



ИБП Piller APOSTAR AR Comfort - брошюра на продукцию. Юниджет

Постоянная ссылка на страницу: <https://www.uni-jet.com/catalog/ibp/online-ibp/piller-apostar-ar-comfort/>



PRODUCT DATA SHEET

APOSTAR AR Comfort

Uninterruptible Power Supply 10kVA - 80kVA

Highlights

- UPS classification VFI SS 111 acc. to IEC 62040 -3 (double conversion)
- very high efficiency
up to 96% in the continuous converter mode and 98% in the line interactive mode
- highly reliable
- redundant and power-parallel configuration of up to 6 units
- 50>60 or 60>50Hz frequency converter as standard



Nothing protects quite like Piller

PRODUCT DATA SHEET

APOSTAR AR Comfort



APOSTAR	AR	Comfort 10	Comfort 15	Comfort 20	Comfort 30	Comfort 40	Comfort 60	Comfort 80
---------	----	------------	------------	------------	------------	------------	------------	------------

Output

Rated power	10kVA	15kVA	20kVA	30kVA	40kVA	60kVA	80kVA
Rated active power	9kW	13,5kW	18kW	27kW	36kW	54kW	72kW
Rated current	14,5A	22A	29A	43,5A	58A	87A	116A
Power factor	0,9	0,9	0,9	0,9	0,9	0,9	0,9
Rated voltage	380-400-415V (adjustable)						
Rated frequency	50 / 60Hz ± 1% (± 2%)						

Input

Rated voltage	380 / 400	380 / 40	380 / 40	380 / 40	380 / 40	380 / 40	380 / 40
Voltage tolerance	±20%	±20%	±20%	±20%	±20%	±20%	±20%
Frequency	40-72Hz	40-72Hz	40-72Hz	40-72Hz	40-72Hz	40-72Hz	40-72Hz
cos φ	0,99	0,99	0,99	0,99	0,99	0,99	0,99

General data

Width	440mm	440mm	440mm	440mm	440mm	500mm	500mm
Depth	850mm	850mm	850mm	850mm	850mm	850mm	850mm
Height	1320mm	1320mm	1320mm	1320mm	1320mm	1600mm	1600mm
Weight	105kg	115kg	120kg	135kg	145kg	195kg	205kg
Backup time	customised						

UPS classification VFI SS 111 acc. to IEC 62040 -3

Interfaces (Standard)

- 1x RS 232, 1 x AS 400, 1 x USB
- Potential free changeover contacts

Options

- external manual bypass in separate cabinet
- additional battery modules for extension of autonomy
- SNMP-adaptor with Ethernet Interface
- DATAWATCH (shut-down)
- remote monitoring- and failure analysis system for UPS units

www.piller.com

