



ИБП Piller APOSTAR AR Single - брошюра на продукцию. Юниджет

Постоянная ссылка на страницу: <https://www.uni-jet.com/catalog/ibp/online-ibp/piller-apostar-ar-single/>



PRODUCT DATA SHEET

APOSTAR AR Single

Uninterruptible Power Supply 3kVA - 10kVA

Highlights

- available as rack mounting and free-standing tower
- rotatable display
- efficiency up to 92%
efficiency of 98% in "line – interactive" mode
- swappable batteries during operation



Nothing protects quite like Piller

PRODUCT DATA SHEET

APOSTAR AR Single



APOSTAR	AR Single 3	AR Single 6	AR Single 10
Output			
Power	3,3 kVA	6kVA	10kVA
Rated active power	2,3kW	4,2kW	9kW
Rated current	14A	26A	43A
Power factor	0,7 (ind.)	0,7 (ind.)	0,9 (ind.)
Rated voltage (adjustable)	220 / 230 / 240V	220 / 230 / 240V	220 / 230 / 240V
Rated frequency	50 / 60Hz	50 / 60Hz	50 / 60Hz
Input			
Rated voltage	164 - 276V	164 - 276V	184 - 276V
Frequency	45 - 65Hz	45 - 65Hz	45 - 65Hz
cos φ	>0,98	>0,98	>0,98
General data			
Width	175mm	175mm	2x 175mm
Depth	520mm	660mm	2x 660mm
Height	455mm	455mm	2x 455mm
Weight	38kg	64kg	1x 30 / 1x 65kg
Backup time	6min (internal battery)	8min (internal battery) or customised	6min
UPS classification	VFI SS 111 acc. to IEC 62040 -3		

Interfaces (Standard)

- RS 232 / USB
- Potentialfree contact

Options

- external manual bypass in separate cabinet
- additional battery modules for extension of autonomy
- SNMP-adaptor with Ethernet Interface
- DATAWATCH (shut-down)
- remote monitoring- and failure analysis system for UPS units

www.piller.com

